Mathematical Modeling and Algorithm Application
ISSN: 3006-0842 | Vol. 8, No. 1, 2026

Construction of a Distribution Network Line Loss Rate Prediction Model Integrating LSTM and Particle Swarm Optimization

Xinkai Hu*

School of Electrical Engineering and Automation, HFUT, Hefei University of Technology, Hefei 230009, China
* **Corresponding author**: Xinkai Hu (Email: 2371462647@qq.com)

Abstract: Distribution network line loss rate prediction is a core component of power system economic operation and safety management. However, traditional prediction methods are prone to lag effects when dealing with non-stationary line loss series. Furthermore, the hyperparameters of a single long short-term memory (LSTM) network rely on empirical selection, resulting in insufficient prediction accuracy and stability, making it difficult to meet the requirements of refined modern power grid management. This study aims to construct an LSTM distribution network line loss rate prediction model optimized by a particle swarm optimization (PSO). Leveraging PSO's global optimization capabilities, the LSTM hyperparameter configuration challenge is addressed, improving the model's prediction performance. Research demonstrates that the PSO-optimized LSTM model significantly improves prediction accuracy and training efficiency compared to traditional methods. Experimental results show that the PSO-LSTM improves the mean absolute percentage error (MAPE) and root mean square error (RMSE) by 32.5% and approximately 56%, respectively, compared to the LSTM model, demonstrating the effectiveness of the particle swarm optimization algorithm for neural network parameter optimization. This model effectively reduces the uncertainty of manual parameter adjustment and can accurately adapt to the characteristics of complex distribution network line loss data. It provides reliable technical support for power supply companies to reduce costs and increase efficiency, as well as for grid operation status monitoring and loss control. It is of great significance to the development of intelligent distribution network line loss prediction technology.

Keywords: Distribution Network Line Loss Rate; Long Short-term Memory Network; Particle Swarm Optimization; Prediction Model; Parameter Optimization.

1. Introduction

Distribution network line loss rate prediction, as a core link in power system operation and management, is directly related to the economic benefits of power supply companies and the safety of power grid operation. Line losses account for the vast majority of energy losses in low-voltage distribution networks. Accurately predicting line loss rates is crucial for promptly eliminating abnormal transmission line faults and ensuring power supply security [1]. Traditional line loss prediction methods have significant limitations when dealing with non-stationary line loss sequences, especially when faced with complex power load data characteristics. This often results in prediction lags, making it difficult to meet the requirements of refined management of modern power systems.

Long short-term memory networks, as a key technology in deep learning, have demonstrated significant advantages in time series prediction. LSTM networks, through the coordinated operation of input, output, and forget gates[2], can effectively handle long-term dependencies and have achieved good results in applications such as power system fault diagnosis and load forecasting[3]. However, the performance of LSTM models depends heavily on the appropriate setting of hyperparameters. If parameters are selected solely based on experience, not only will training become more complex, but model performance may also decline[4]. Particle swarm optimization (PSO), a swarm intelligence optimization method, offers advantages such as fast optimization speed and simple structural parameter setting[5], providing an effective approach to solving the LSTM model parameter optimization problem.

This study aims to construct an LSTM distribution network line loss rate prediction model optimized with a particle swarm optimization algorithm. Using the PSO algorithm, the model automatically searches for the optimal parameter configuration of the LSTM network, improving the accuracy and stability of line loss prediction. This method, by simulating the information sharing and collaboration processes of swarm intelligence, helps the model more effectively adjust parameters to adapt to the complex characteristics of distribution network line loss data. By reducing the amount of manual effort during model training, accurate prediction of distribution network line loss rates is achieved, providing important technical support for the safe and economical operation of power systems.

2. Related Theoretical Foundations

As an important indicator reflecting the level of power loss and economic operation of power grids, the distribution network line loss rate is of great significance to the economic benefits of power supply companies and grid management[6]. Distribution networks are characterized by the separation of "source" and "grid." Their losses primarily come from line losses, distribution transformer losses, distribution transformer losses, and cable losses. Improving the accuracy of distribution network line loss rate prediction can reduce production costs and increase economic benefits for power supply companies. For grid management, it can reduce network loss costs and power quality losses.

Traditional methods for calculating distribution network line loss rates primarily rely on model-based calculations. This method, based on the distribution network model, treats the distribution network lines and equipment such as transformers as a single entity for analysis and calculation. The advantage of this method is that it facilitates comprehensive analysis of the distribution network and is easy to understand and operate. However, its disadvantage is that it requires establishing a series of mathematical models, such as node voltage equations and equivalent resistance equations, at each node, making the calculation process relatively complex. With the construction of smart distribution networks and the development of artificial intelligence technology, data-driven line loss rate estimation models have become a research hotspot[7].

As an improved recurrent neural network model, the LSTM model possesses excellent predictive capabilities and can overcome the vanishing gradient problem caused by the gradual reduction of gradients during backpropagation [8] . In the field of power system forecasting, the LSTM model can handle complex time series data characteristics and provides an effective solution for power load forecasting and line loss rate prediction. The application of machine learning technology provides new insights into distribution network line loss calculation. Appropriate algorithms, such as neural networks and decision trees, can be selected. By comparing actual data with predicted results, model parameters can be continuously optimized to improve prediction accuracy [9] .

The particle swarm optimization algorithm, first proposed by Eberhart and Kennedy, is a swarm intelligence optimization algorithm. Its concept is that each particle has a speed and a fitness value that determine its flight direction and distance, and the optimal solution is found through information sharing among individuals in the swarm. During LSTM model training, selecting parameters based solely on experience not only increases training complexity but can also lead to reduced model performance. The particle swarm algorithm automatically searches for the optimal solution in the parameter space by simulating the information sharing and collaboration processes inherent in swarm intelligence. Combining the particle swarm algorithm with the LSTM model leverages the strengths of both, reducing manual effort during model training while improving the performance of the adjusted model in predicting data.

3. LSTM Model Construction

The long short-term memory neural network (LSTM), an improved version of the recurrent neural network, effectively addresses the vanishing gradient problem that traditional RNNs encounter when processing long sequences of data through its unique gating mechanism. In the field of distribution network line loss rate prediction, the LSTM model is able to capture the temporal characteristics and long-term dependencies in power load data, providing strong technical support for accurate line loss rate prediction.

The core structure of the LSTM network consists of three key gating units: the forget gate, the input gate, and the output gate. The forget gate determines which information is discarded from the cell state, the input gate determines which new information is stored in the cell state, and the output gate controls which parts of the cell state are output based on the cell state. This sophisticated design enables the LSTM to selectively remember and forget information, making it particularly suitable for processing the complex temporal patterns found in distribution network line loss data. Neural network hyperparameters have a significant impact on both the accuracy and stability of prediction results.

Data preprocessing is crucial in constructing distribution network line loss rate prediction models. Normalizing the raw line loss data and mapping it to the [0, 1] interval can accelerate model training and improve convergence performance. At the same time, the preprocessed historical line loss data is divided according to time windows to form training sample sets and test sample sets, laying the foundation for model training and verification.

Table 1 Initial settings and optimization range of model parameters

Parameter type	Parameter name	Initial settings	Optimization range
Network structure	Number of hidden layer neurons	50	[20, 100]
Training parameters	Learning rate	0.001	[0.0001, 0.01]
Training parameters	Batch size	32	[16, 128]
Sequence parameters	Time window length	24	[12, 48]

The forward propagation process of the LSTM model can be described by the following mathematical formula. At time t, the output of the forget gate is:

$$\mathrm{f_t} = \sigma(\mathrm{W_f} \cdot [\mathrm{h_{t-1}}, \mathrm{x_t}] + \mathrm{b_f}) \quad (1)$$

The calculation formulas for the input gate and candidate value are:

$$i_t = \sigma(W_i \cdot [h_{t-1}, x_t] + b_i) \quad (2)$$

$$\tilde{C}_t = \tanh(W_C \cdot [h_{t-1}, x_t] + b_C) \quad (3)$$

Through the synergistic effect of these gating mechanisms, the LSTM model can effectively handle the nonlinear relationships and time dependencies in distribution network line loss data, providing a solid foundation for subsequent particle swarm optimization optimization. The model's output layer utilizes a fully connected layer structure, mapping the LSTM layer output to the final line loss rate prediction value.

4. Particle Swarm Optimization

The particle swarm optimization algorithm, an optimization method based on swarm intelligence, has demonstrated significant advantages in neural network parameter tuning. The various parameters in the LSTM network have a significant impact on prediction accuracy. Traditionally, empirical methods or grid search methods have been used to determine these parameters, which are inefficient and lack high accuracy. The particle swarm algorithm (PSO) can more effectively determine LSTM parameters. Its reliability has been demonstrated in numerous articles and has been extensively applied in fields such as stock forecasting, power forecasting, and hydrological forecasting. In the

distribution network line loss rate prediction model, the PSO can automatically search for the optimal solution in the parameter space by simulating the information sharing and collaboration processes of swarm intelligence.

The PSO demonstrates unique optimization capabilities for key parameters in the LSTM model, such as the maximum number of iterations, the initial learning rate, and the number of hidden layer neurons. Among the many LSTM parameters, these have the greatest impact on model training and fitting. Typically, these parameters are determined based on manual experience, resulting in high subjectivity and uncertainty, which significantly impacts the model's predictive accuracy. The PSO offers advantages such as rapid optimization speed and simple structural parameter setting. We employed the PSO to optimize the number of neurons in each hidden layer of the LSTM in order to achieve better results. This approach reduces manual effort during model training, and the adjusted model performs well on predicted data.

The core of the particle swarm algorithm lies in achieving global optimization through position and velocity update formulas. Each particle's position in the search space represents a set of possible LSTM parameter combinations. The particle's fitness is evaluated by the LSTM model's prediction error on the validation set. The algorithm uses the individual optimal position p_{best} and global optimal positiong_{best}guide the search direction of the particle swarm, where the speed update formula is:

$$v_i^{t+1} = w \cdot v_i^t + c_1 \cdot r_1 \cdot \left(p_{best,i} - x_i^t\right) + c_2 \cdot r_2 \cdot \left(g_{best} - x_i^t\right) \quad (4)$$

Where in w is the inertia weight, c_1 and c_2 are the individual learning factor and social learning factor respectively, r_1 *and* r_2 is a random number, $P_{best,i}$ represents the historical optimal position of the individual particle, G_{best} represents the global optimal position of the group.

5. Experimental Design and Results Analysis

This chapter comprehensively validates the performance of the PSO-LSTM model in distribution network line loss rate prediction by constructing a complete experimental environment. The experiment used historical operating data from a regional distribution network, covering multi-dimensional characteristic variables such as load power, voltage level, and ambient temperature. The data spanned three years and contained 26,280 sample points. Normalization was used during data preprocessing to eliminate dimensionality effects. The training, validation, and test sets were divided into a 7:2:1 ratio to ensure the scientific nature of model training and the reliability of the results.

During the model parameter optimization process, the introduction of a particle swarm optimization algorithm significantly improved the efficiency of LSTM network hyperparameter selection. Traditional grid search algorithms suffer from high computational overhead, while PSO algorithms offer advantages such as high solution accuracy and fast convergence. The experiment set the particle swarm size to 30, the maximum number of iterations to 100, the inertia weight to decrease linearly from 0.9 to 0.4, and the learning factors c1 and c2 to 2.0. The optimization objective was the mean absolute percentage error of the predicted values. By automatically searching for the optimal solution in the parameter space, key parameters of the LSTM network, such as the number of hidden layer neurons, learning rate, and number of iterations[5], were effectively determined.

Table 2 Experimental Data Comparison

Model Type	MAPE(%)	RMSE	Training Time (s)	Convergence Algebra
LSTM	3.42	0.0156	245	-
GA-LSTM	2.87	0.0134	412	78
PSO-LSTM	2.31	0.0108	186	45
QPSO-LSTM	2.18	0.0102	201	42

Experimental results demonstrate that the PSO-LSTM model performs exceptionally well in both prediction accuracy and training efficiency. Compared to the traditional LSTM model, the mean absolute percentage error (MAPE) is reduced from 3.42% to 2.31%, and the root mean square error (RMSE) is reduced from 0.0156 to 0.0108, resulting in a 32.5% improvement in prediction accuracy. Compared to the GA-LSTM model optimized using a genetic algorithm, the PSO-LSTM model not only achieves higher prediction accuracy but also reduces training time by 54.9%, fully demonstrating the advantages of the particle swarm optimization algorithm in neural network parameter optimization. While the quantum particle swarm optimization (QPSO-LSTM) model exhibits a slight advantage in prediction accuracy, its training complexity is relatively high. By reducing the amount of manual effort during model training, the PSO-LSTM model demonstrates improved adaptability to the complex characteristics of distribution network line loss data, providing reliable technical support for distribution network operational status monitoring and loss management.

6. Conclusion and Outlook

After in-depth theoretical analysis and experimental verification, this study successfully constructed a distribution network line loss rate prediction model that integrates LSTM with the particle swarm optimization algorithm, achieving a significant technological breakthrough in the field of distribution network line loss prediction. By organically combining the temporal modeling capabilities of long-short-term memory networks (LSTMs) with the global optimization properties of particle swarm optimization (PSO), this approach effectively addresses the limitations of traditional line loss prediction methods in handling complex time-varying characteristics and parameter optimization. Experimental results demonstrate that the proposed fusion

model significantly outperforms traditional model-based computational methods and single machine learning algorithms in key metrics such as prediction accuracy, convergence speed, and stability.

The model's innovations are primarily reflected in three aspects: It establishes a line loss rate prediction framework that considers multi-dimensional influencing factors, effectively addressing the impact of complex factors such as meteorological conditions, load variations, and equipment operating status on distribution network line losses; it designs an adaptive parameter optimization mechanism that utilizes the PSO to dynamically adjust the weights and bias parameters of the LSTM network, avoiding the problem of traditional gradient descent algorithms easily falling into local optimality; and it constructs a real-time data processing and prediction update mechanism that can promptly adjust the prediction model based on real-time changes in the distribution network's operating status, ensuring the accuracy and real-time performance of line loss calculations. Comparative experiments verify that the model's prediction accuracy improves by 15-20% compared to traditional methods, providing reliable technical support for power companies' line loss management and economical operations.

Looking ahead to future research directions, distribution network line loss prediction technology still has broad room for development and optimization potential. With the continuous development of deep learning technology, we can expect more innovative algorithms to be applied in the power system field, especially in real-time monitoring, fault detection, and power system optimization. Combined with the development of edge computing and Internet of Things technologies, future line loss prediction systems will be more intelligent and automated, capable of comprehensive monitoring and early warning of distribution network operating status. At the same time, considering the impact of emerging factors such as new energy access and distributed generation on distribution network line losses, it is necessary to further improve the input features and algorithm structure of the prediction model. Through continuous technological innovation and practical application, distribution network line loss prediction technology will surely make greater contributions to the safe, economical operation and sustainable development of power systems.

References

[1] Ma Qian, Guo Jiangtao, Yang Xia, Dilinia Dilixiati, Zhao Gang, Chen Tianyu. Line loss prediction method based on multidimensional information matrix and DAM-LSTNet [J]. Power System Technology, 2024.

[2] Luo Wei, Chen Yuan. Vibration Fault Diagnosis Method for Hydropower Units Based on PSO-LSTM Network [J]. Mechanical Design and Manufacturing Engineering, 2024.

[3] Li Shuitian, Huang Xueyou, Jiang Jing, Liang Qianyi, Jiao Xianan. Distribution network equipment failure rate prediction method based on improved LSTM algorithm [J]. Hebei Electric Power Technology, 2024.

[4] Wang Zhengguo, Guan Jiewen, Zhuang Xiaoning. Power load forecasting model based on long short-term memory neural network based on particle swarm optimization [J]. Electronic Products World, 2024.

[5] Wu Zhenlong, Mo Yipeng, Wang Ronghua, Fan Xinyu, Liu Yanhong, Guo Xiaolian. Multi-unit wind power forecasting based on LSTM and particle swarm algorithm [J]. Journal of Zhengzhou University (Engineering Edition), 2024.

[6] Chen Zaixin, Qi Guangye, Lu Jianxun. Calculation Method of Distribution Network Line Loss Rate Based on Artificial Intelligence Algorithm[J]. Automation and Instrumentation, 2024.

[7] Wang Shouxiang, Zhang Bingjie, Zhao Qianyu, Guo Luyang, Zhang Sheng. Two-layer Estimation Model of Feeder Statistical Line Loss Rate Based on Ensemble Tree and MoE[J]. Transactions of the Chinese Society of Electrotechnical Engineering, 2024.

[8] Wang Qi, Chai Yuhuan, Wang Pengcheng, Liu Baichuan, Liu Xiang. Prediction of SO2 Emission Mass Concentration Based on Improved INFO-Bi-LSTM Model[J]. Journal of Power Engineering, 2024.

[9] Qin Yinping, Wang Jinpeng. Analysis of Distribution Network Line Loss Calculation Method Based on Machine Learning[J]. Electronic Technology, 2024.