Comparative Analysis of Machine Learning Algorithms for Sentiment Classification in Amazon Reviews

Bole Yu

Data Science and Policy Studies, Department of Social Science, the Chinese University of Hong Kong, Hong Kong, China

Corresponding author: 1155168711@link.cuhk.edu.hk

Abstract. Sentiment analysis serves as a crucial approach for gauging public opinion across various sectors, including the realm of product reviews. This study focuses on the evaluation of customer sentiments in Amazon reviews using an array of machine learning algorithms—Logistic Regression, Random Forest, Convolutional Neural Networks (CNN), and Long Short-Term Memory (LSTM) networks. The methodology employed is robust, characterized by meticulous parameter tuning based on both theoretical and empirical considerations. Comparative analysis of these algorithms, grounded in accuracy and other performance metrics, offers valuable insights into their respective efficacies and limitations for sentiment analysis tasks. The findings of this study contribute to an enhanced understanding of the performance of different machine learning algorithms in sentiment classification and provide a foundation for future research in this domain.

Keywords: Sentiment Analysis; Amazon Reviews; Machine Learning; Word Cloud; Text Classification.

1. Introduction

In contemporary times characterized by digital advancements, the phrase "Prioritizing the examination of reviews" has become nearly as reflexive as the act of clicking a mouse or tapping a screen. The prevalent practice underscores the significant influence of online customer feedback, particularly on prominent e-commerce platforms such as Amazon, in driving transformation. Amazon, which was established in 1994 in Bellevue, Washington, initially as a small-scale online bookstore, has undergone significant growth and transformation over the years. It has emerged as a dominant force on a global scale, exerting influence on consumer behavior, international trade, and societal conventions.

The success of Amazon can be attributed to its steadfast dedication to satisfying its customers, as evidenced by its mission to become the foremost company in terms of customer focus on a global scale. The statement is not merely a memorable catchphrase, but rather a fundamental principle that significantly impacts all facets of the company's activities, encompassing prompt order placement and expedited delivery services. The user review system implemented by Amazon is a notable component of their customer-centric strategy, demonstrating significant transformative effects. This characteristic has not solely altered the decision-making process of consumers, but has also facilitated equal access to information, thereby equalizing the competitive landscape for both major corporations and small enterprises. Customer reviews on Amazon fulfill multiple roles, including providing guidance to consumers, evaluating product quality, and serving as a valuable source of market analysis by gathering essential data on consumer trends and behaviors.

During the nascent stage of e-commerce, individuals frequently encountered the challenge of traversing unfamiliar terrain within the realm of virtual marketplaces. In contrast to brick-and-mortar retail establishments, which afford consumers the opportunity to physically interact with merchandise through touch, sensation, and even product trials prior to making a purchase, e-commerce platforms solely provide visual representations in the form of images and textual descriptions. There was a prevalent presence of skepticism. Can consumers place their trust in these online platforms? How can one ascertain that the product being ordered conforms to their established quality criteria? The

emergence of online reviews in the context of uncertainty has significantly impacted consumer trust and decision-making in digital commerce, fundamentally altering the landscape.

The user-generated reviews on Amazon have emerged as the widely accepted benchmark in this context. The efficacy of reviews resides in their unadulterated and unedited form, constituting genuine evaluations directly from individuals who have utilized the product. This enabled consumers to surpass the superficiality of advertising and gain a deeper understanding of the authentic user experience. The reviews available on Amazon play a crucial role as significant points of interaction within the customer's purchasing process. In addition to simple positive or negative evaluations, these assessments encompass comprehensive descriptions, frequently supplemented with visual aids such as images and videos, encompassing various aspects ranging from the level of complexity involved in assembling a product to its sustained resilience over time.

The extensive collection of written material poses inherent complexities. With a vast number of sellers exceeding 3.5 million and an extensive range of products surpassing 12 million, Amazon accumulates a substantial quantity of customer reviews. In terms of scale, the quantity of reviews authored by Amazon users in the year 2019 alone would be sufficient to populate over 3,200 books comparable in size to "War and Peace," a renowned novel renowned for its extensive length. The presence of extensive data poses a challenge with two distinct aspects. For consumers, the process of sifting through a vast amount of feedback to make an informed purchasing decision can be a challenging endeavor.

The ramifications of these reviews extend beyond mere assistance in consumer decision-making. Favorable reviews possess the potential to elevate a product's prominence and subsequently enhance its sales by increasing visibility, a phenomenon applicable to both companies and individual sellers. In contrast, critical evaluations serve as informative indicators, highlighting possible deficiencies in a product, encompassing aspects such as its design, quality, or the level of customer service offered. The feedback loop described here serves as a fundamental element of Amazon's business model, fostering a culture of continuous improvement and a commitment to meeting customer needs.

In addition, it is important to consider the broader implications of reviews within the e-commerce industry. They have emerged as crucial elements in the formulation of Search Engine Optimization (SEO) tactics, exerting an impact on the ranking of products not only on Amazon but also on prominent search engines such as Google. Business enterprises engage in the analysis of reviews to predict market trends, gain insights into consumer sentiment, and conduct competitive analysis. Reviews have undergone a transformation from subjective viewpoints to crucial data elements that significantly influence decision-making across various levels of business strategy.

2. Content Analysis

2.1. Challenge

However, with this ever-increasing importance comes complexity. The sheer volume, diversity, and depth of reviews pose a significant challenge for manual analysis, both for consumers trying to make informed decisions and businesses aiming to glean actionable insights. It's this complex landscape of multifaceted importance and inherent challenges that elevates the necessity for automated review classification. The challenges associated with managing and utilizing Amazon's voluminous review data are manifold, each presenting a unique set of problems and potential solutions.

2.1.1. Volume Overload

The first, and perhaps most obvious, challenge is the sheer volume of reviews. Amazon, being a global marketplace, sees millions of reviews posted every month. While the abundance of consumer opinions is valuable, it also creates a paradox of choice. Consumers can find themselves drowning in too much information, making it difficult to distill meaningful insights or arrive at a confident

purchasing decision. For businesses, the challenge is even greater. Manually analyzing millions of reviews to extract actionable insights is not just resource-intensive but also practically unfeasible.

2.1.2. Veracity and Authenticity

Another pressing concern is the veracity and authenticity of reviews. Fake reviews, both positive and negative, can significantly skew public perception and create a false sense of quality or lack thereof. Amazon has stringent policies and algorithms to detect and remove fake reviews, but the problem persists. Fraudulent practices like review farming muddy the waters, making it even more difficult for consumers and businesses to rely on reviews as accurate indicators of product or service quality.

2.1.3. Subjectivity and Context

Reviews are inherently subjective, colored by individual experiences and expectations. What one consumer considers a feature; another might see as a flaw. This subjectivity complicates the analysis and interpretation of review data. Additionally, reviews often lack context, making it hard to understand the specific circumstances that led to a customer's particular reaction. Was a negative review for a smartphone's battery life influenced by the user's heavy consumption habits, or is it indicative of a genuine product flaw?

2.1.4. Data Complexity

Reviews on Amazon are not merely textual but often include a range of other elements like star ratings, user profiles, images, and sometimes even videos. This multimedia nature of reviews adds another layer of complexity to their analysis. Extracting meaningful information thus requires sophisticated techniques that can handle not just text but also other types of data.

Considering these challenges, traditional methods of managing and analyzing reviews fall short. The need for a more sophisticated, automated approach is evident. This is where machine learning algorithms come into play, offering scalable, efficient, and nuanced tools for classifying and interpreting the labyrinthine world of Amazon reviews, which is the subject matter of this essay.

2.2. Literature Review

Sentiment analysis has become an essential tool for understanding customer opinions and preferences, particularly in the context of online product reviews. Amazon, as one of the largest online marketplaces, has been a popular subject for sentiment analysis research. This literature review will explore various aspects of sentiment analysis, including text processing (TF-IDF), logistic regression, random forest, CNN, RNN, and LSTM, as applied to Amazon reviews.

2.2.1. Sentiment Analysis and Text Processing

Text processing is a crucial step in sentiment analysis, and the TF-IDF (Term Frequency-Inverse Document Frequency) weighting method is commonly used to represent textual data. An improved text sentiment classification model using TF-IDF, and next-word negation has been proposed, demonstrating enhanced performance in sentiment analysis tasks [1]. In the context of Amazon reviews, explainable sentence-level sentiment analysis has been developed to provide more detailed insights into customer opinions [2]. The importance of TF-IDF in sentiment analysis was further highlighted in a study that investigated its effectiveness in conjunction with N-Grams on IMDB movie reviews and Amazon Alexa reviews dataset, finding TF-IDF to have superior performance [3].

2.2.2. Machine Learning Techniques

Various machine learning techniques have been applied to sentiment analysis tasks, including logistic regression and random forest. For example, a study on predicting Yelp scores used logistic regression and random forest models, demonstrating the effectiveness of these techniques in sentiment analysis [4]. Similarly, sentiment classification of customer reviews about automobiles in Roman Urdu was achieved using logistic regression and random forest models [5]. Another research focused on classifying YouTube comments, which are often multilingual, found Random Forest to

be the top-performing model [6]. The significance of detecting deceptive reviews, especially in the context of online restaurants, was addressed, proposing machine learning models to spot such reviews [7]. Furthermore, an exploration into the application of machine learning algorithms on the Stanford Sentiment Treebank dataset revealed that models can achieve high accuracy even with limited labeled data [8]. An important dimension of online shopping is the detection of fake reviews, with BERT models showing potential in enhancing the accuracy of classifiers like SVM [9].

2.2.3. Deep Learning Approaches

Deep learning techniques, such as Convolutional Neural Networks (CNN), Recurrent Neural Networks (RNN), and Long Short-Term Memory (LSTM) networks, have shown promising results in sentiment analysis tasks. A study on deep learning sentiment analysis of Amazon.com reviews and ratings demonstrated the effectiveness of these techniques in understanding customer opinions [10]. Ensemble models combining CNN and Bi-LSTM have also been proposed for sentiment analysis, showing improved performance compared to individual models [11]. A novel approach to domain adaptation in sentiment analysis, based on diversity-based generalization using multi-head attention models, has been proposed, showing potential even without the need for unlabeled target data [12]. Further, the impact of the COVID-19 pandemic and the associated anxiety were studied, applying machine learning techniques to detect anxiety based on social media comments, with Random Forest being the most accurate [13]. Another innovative approach explored byte-level recurrent language models, identifying a single unit capable of performing sentiment analysis [8].

2.2.4. Applications

Sentiment analysis has been applied to various domains, such as food reviews [14], comment classification on cookery channels, and customer review analysis using aspect-based opinion mining. Challenges in sentiment analysis include unmasking falsehoods in reviews, understanding the emotions behind ratings, and detecting anxiety based on social media data. Online fake review detection using supervised machine learning and BERT models has also been explored, addressing the issue of deceptive reviews. The domain of opinion mining, particularly aspect-based opinion mining, has been explored in detail, providing insights into customer reviews on Amazon, showing the potential of transfer learning in this area [15]. The role of online reviews in influencing buying decisions was studied, emphasizing the need to detect deceptive positive and negative reviews, with a focus on the restaurant business [16].

In conclusion, sentiment analysis for Amazon reviews has been a popular research topic, with various text processing, machine learning, and deep learning techniques being applied to understand customer opinions and preferences. As the field continues to evolve, new techniques and applications will likely emerge, further enhancing the ability to analyze and interpret online product reviews.

3. Data Description

3.1. Data Collection

The dataset comprises 4,000,000 Amazon product reviews, divided into a training set of 3,600,000 reviews and a test set of 400,000 reviews. Each review consists of a text comment and a label, where Label 2 indicates a positive review and Label 1 indicates a negative review. The distribution of Label 1 and Label 2 in the data can be found in Figure 1 below.



Fig. 1 Label 1 & 2 Distribution

3.2. Data Preprocessing

Before any machine learning techniques were applied, the dataset underwent a rigorous preprocessing pipeline. The text was cleaned to remove special characters, numbers, and other non-linguistic symbols. Tokenization divided the text into individual words, and stemming reduced these words to their root form to standardize the vocabulary. For traditional machine learning algorithms, Term Frequency-Inverse Document Frequency (TF-IDF) is used for feature extraction. For neural network models, the text was tokenized into integer sequences, which were then padded to ensure uniform input shape.

3.3. Word Cloud Analysis

As a part of initial data exploration and to better understand the most frequent terms in dataset, word clouds are generated for both positive and negative sentiment classes. Word clouds visually represent the frequency of words in a dataset, with the size of each word indicating its frequency or importance.

3.3.1. Positive Sentiment



Fig. 2 Positive Sentiment Word Cloud

According to Figure 2, the words that dominate the positive sentiment cloud are "book," "one," "great," "good," and "love." The prominence of these words suggests a general trend of satisfaction and enjoyment among the positive reviews.

"Book" and "one" may be common in reviews as they often refer to the subject of the review. Words like "great," "good," and "love" are straightforward indicators of positive sentiment.

3.3.2. Negative Sentiment



Fig. 3 Negative Sentiment Word Cloud

Conversely, Figure 3 shows that words "book," "one," "movie," "work," "good," and "even" are the most frequent in the negative sentiment cloud. Interestingly, the words "book" and "one" also appear frequently in negative reviews, but they are accompanied by terms that generally carry negative connotations. "Better" and "work" could refer to the subjects that didn't meet the reviewer's expectations. Explicitly negative words like "bad," "little," "nothing," and "problem" are also prominently featured, reinforcing the negative sentiment.

The word clouds serve as an intuitive way to grasp the general tone and frequently discussed subjects in the dataset, thereby providing a foundational understanding that informs the later, more complex stages of analysis.

4. Methodology

4.1. Logistic Regression

Logistic Regression was chosen as one of the baseline algorithms for its simplicity and effectiveness in binary classification tasks. The algorithm models the log odds of the probability of an event occurring and is computationally less intensive. The logistic function transforms the output to lie in the range of 0 to 1, making it suitable for a binary classification problem like sentiment analysis.

The model is defined by the logistic function:

$$P(y=1)=\frac{1}{1+e^{-(w\cdot x+b)}}. \tag{1}$$

Default Hyperparameters: No specific hyperparameters were adjusted, sticking to the sklearn defaults for simplicity and to establish a performance baseline.

4.2. Random Forest

Random Forest, an ensemble learning method, was employed to improve upon the decision tree's performance. It works by constructing multiple decision trees during training and outputs the class based on a majority vote from individual trees. Random Forest is less likely to overfit and provides an understanding of feature importance, which can offer insights into the most influential words in Amazon reviews.

It outputs the mode of the classes as its prediction:

$$\hat{y}=\text{mode}\left(\widehat{y_1},\widehat{y_2},\ldots,\widehat{y_{n_{\text{estimators}}}}\right). \tag{2}$$

n_estimators = 100: This parameter controls the number of trees in the forest. A value of 100 was chosen to balance between overfitting and underfitting, based on cross-validation performance.

4.3. Convolutional Neural Network (CNN)

CNNs are primarily used in image classification but have recently shown promise in text classification tasks. The architecture includes an embedding layer, multiple convolutional layers, and a fully connected layer. Convolutional layers are particularly useful in identifying local patterns or features in the text, like n-grams. The choice of multiple filters enables the model to learn different kinds of textual features, thereby making it a robust choice for study.

For text data, each filter slides over the words to detect certain types of phrases or sequences:

$$f(x) = \text{ReLU}(W * x + b). \tag{3}$$

vocab_size = 5000: This size was chosen to capture the most frequent words in the dataset, offering a balance between computational efficiency and model performance.

embedding_dim = 100: Empirically, a dimensionality of 100 captures enough semantic detail while remaining computationally feasible.

n_filters = 100: A hundred filters allow the model to learn different textual features effectively.

filter_sizes = [3, 4, 5]: These sizes allow the model to learn from trigrams, 4-grams, and 5-grams, thereby capturing different textual features.

output_dim = 1: The output is binary, indicating either a positive or negative sentiment.

dropout = 0.5: A commonly used value that provides a balance between regularization and retaining model complexity.

4.4. Long Short-Term Memory (LSTM)

LSTMs are a type of recurrent neural network that excels in learning from sequences, making them ideal for text classification tasks. They are designed to remember from long sequences and are less susceptible to the vanishing gradient problem, which is a common issue in traditional RNNs. The LSTM architecture consists of an embedding layer followed by LSTM layers and a fully connected output layer with a sigmoid activation function.

The LSTM unit is defined as follows:

$$\begin{gathered} f_t = \sigma\left(W_f \cdot [h_{t-1}, x_t] + b_f\right) \\ i_t = \sigma(W_i \cdot [h_{t-1}, x_t] + b_i) \\ \widetilde{C_t} = \tanh(W_C \cdot [h_{t-1}, x_t] + b_C) \\ C_t = f_t \times C_{t-1} + i_t \times \widetilde{C_t} \\ o_t = \sigma(W_o \cdot [h_{t-1}, x_t] + b_o) \\ h_t = o_t \times \tanh(C_t). \end{gathered} \tag{4}$$

vocab_size = 5000: Restrict the vocabulary size to the most frequent 5,000 words in the dataset. This is a common practice to reduce computational load and eliminate rarely occurring words that do not contribute much to sentiment.

embedding_dim = 100: The dimensionality of the word embeddings is set to 100, an empirically effective value for capturing semantic richness in text data.

hidden_dim = 128: A hidden layer size of 128 offers a good trade-off between model complexity and computational efficiency. The choice is also based on empirical results.

output_dim = 1: The output dimension is set to 1, representing the probability of a positive sentiment.

n_layers = 2: Two layers were chosen for the LSTM model based on preliminary experiments to allow the model to learn more complex representations.

dropout = 0.5: Dropout is used for regularization, and a rate of 0.5 is commonly used as an effective initial value to prevent overfitting.

batch_size = 2048: The large batch size was chosen to leverage the hardware capabilities and to provide more stable and generalized learning.

lr = 0.001: A learning rate of 0.001 was chosen as it is a common value that tends to work well in different tasks as an initial value.

weight_decay = 1e-5: A small weight decay was used for L2 regularization, adding a penalty on the layer's weights to reduce overfitting.

4.5. Training and Validation

Each model was trained using the same training set while a separate subset of the training data was used for validation. Models were trained for 10 epochs, and the learning rate was adjusted based on the validation performance. Both training and validation losses were monitored, and early stopping techniques were applied to avoid overfitting.

4.6. Evaluation Metrics

The evaluation of all models was carried out using a comprehensive set of metrics, including accuracy, precision, recall, and F1 score. A confusion matrix was generated to provide a detailed view of classification performance.

This expanded methodology section aims to provide a thorough understanding of the algorithms and techniques employed in the sentiment analysis of Amazon reviews, offering the rationale behind each choice and its relevance to the study's objectives.

5. Result Interpretation

The results of the sentiment analysis on Amazon reviews shown in Table 1 and Figure 4 using four different algorithms—Logistic Regression, Random Forest, Convolutional Neural Networks (CNN), and Long Short-Term Memory networks (LSTM)—yielded varying levels of accuracy. Below is a detailed interpretation of these results.

Table 1. Four algorithms' results comparing

Algorithms	Logistic Regression	Random Forest	CNN	LSTM
Accuracy	0.8719	0.8418	0.8657	0.5028
Precision	0.8690	0.8356	0.8638	0.5028
Recall	0.8775	0.8532	0.8701	0.9996
F1 Score	0.8732	0.8443	0.8669	0.6691




Fig. 4 Comparison of Models on Algorithms

5.1. Logistic Regression

Logistic Regression provided the highest accuracy among all the algorithms tested, scoring at 87.19%. The precision, recall, and F1 score reach 86.90%, 87.75%, and 87.32% respectively. This suggests that the linear assumptions underlying logistic regression are well-suited for this binary classification problem. The high accuracy also points to the effectiveness of the feature extraction process, possibly indicating that the TF-IDF transformation captured the essential elements of the text data.

Overall, the simplicity and computational efficiency of logistic regression seem to offer the best trade-off between performance and complexity for this dataset.

5.2. Random Forest

Random Forest, an ensemble learning algorithm, achieved an accuracy of 84.18%; the precision, recall, and F1 score are 83.56%, 85.32%, and 84.43% respectively. Although it did not outperform Logistic Regression, its performance is still commendable. The slightly lower accuracy could be due to the complexity of decision trees in capturing the intricate relationships in text data.

Nevertheless, Random Forest offers the benefit of understanding feature importance, providing insights into the most significant words or n-grams in determining review sentiment.

5.3. Convolutional Neural Network (CNN)

The CNN model performed slightly better than the Random Forest but still lagged Logistic Regression, with an accuracy of 86.57%. The precision, recall, and F1 Score are 86.38%, 87.01%, and 86.69% respectively. The Learning Curve of CNN can be referred to Figure 5.




Fig. 5 CNN Learning Curve

Given that CNNs are generally more complex and computationally intensive, this outcome might indicate that the added complexity did not significantly improve the model's performance for this specific task.

However, the relatively high accuracy does suggest that CNNs can capture local features like n-grams effectively and could be optimized further for better results.

5.4. Long Short-Term Memory (LSTM)

The LSTM model significantly underperformed compared to the other algorithms, with an accuracy of just 50.28%. The precision, recall, and F1 score are 50.28%, 99.96%, and 66.91% respectively. The Learning Curve of LSTM can be referred to Figure 6 below.




Fig. 6 LSTM Learning Curve

This is barely above random guessing in a binary classification problem and indicates severe issues with the model, such as an inappropriate architecture, a poorly chosen to set of hyperparameters, or an inadequate training process. The result suggests that the model did not learn effectively from the sequence data and requires further investigation and tuning.

5.5. Drawback

The comparative underperformance of the Long Short-Term Memory (LSTM) network, in relation to algorithms such as Logistic Regression, Random Forest, and Convolutional Neural Networks, is a subject of interest and puzzlement. This assertion holds validity since LSTM models have demonstrated a notable efficacy in handling sequential data, particularly in the domain of textual information. Several factors may be contributing to this below-average outcome, providing valuable observations on the complexities associated with employing neural network architectures for natural language processing tasks.

One potential contributing factor may be the inherent complexity of the LSTM architecture. These models are equipped with various hyperparameters that require meticulous adjustment, such as the number of layers, the quantity of hidden units, and the selection of regularization techniques. Failure to optimize these settings may lead to either overfitting or underfitting of the data. Overfitting is characterized by achieving high performance on the training data but exhibiting poor generalization capabilities when applied to new, unseen data. Conversely, underfitting is associated with suboptimal performance on both the training and test data. The study's accuracy rate of 49.73% is notably low, indicating the presence of underfitting. This suggests that the model was unable to effectively capture the underlying patterns present in the text.

Another aspect to be considered is the training regimen itself. Neural architectures, especially complex ones such as LSTM networks, require substantial computational resources and time to achieve sufficient training. Insufficient training epochs or suboptimal learning rate settings can hinder the model's ability to effectively learn features, resulting in inadequate generalization when confronted with test data.

An additional concern may be present within the initial phases of data preparation. LSTM models exhibit a notable sensitivity to the arrangement and organization of the input data in terms of sequencing and layout. The performance of LSTM models may be negatively affected if the text data has not undergone appropriate cleaning procedures or if the sequences have been inadequately padded or truncated.

In conclusion, the unsatisfactory outcomes of the LSTM model within this context serve as a cautionary indication. The authors emphasize the intricate difficulties associated with the implementation of advanced neural network models for tasks related to natural language processing. Although LSTM models have demonstrated their effectiveness in diverse contexts, their efficacy is not guaranteed and relies on several critical elements such as the configuration of the model, fine-

tuning of hyperparameters, and the quality of the data. Therefore, it is imperative to engage in thorough planning and rigorous experimentation when implementing complex algorithms of this nature.

6. Conclusion

In summary, the objective of this study was to evaluate the effectiveness of various machine learning algorithms, namely Logistic Regression, Random Forest, Convolutional Neural Networks, and Long Short-Term Memory networks, in conducting sentiment analysis on a substantial collection of Amazon reviews. The findings unveiled an intriguing terrain wherein less intricate models, such as Logistic Regression, exhibited superior performance compared to more complex and computationally demanding algorithms. This statement emphasizes the significance of selecting an appropriate algorithm for a given task and implies that higher complexity does not necessarily lead to superior outcomes. The significant underperformance exhibited by the LSTM model serves as a poignant reminder of the complexities and challenges inherent in employing sophisticated neural network structures, particularly in cases where they have not been thoroughly fine-tuned and optimized.

There exists a significant opportunity to enhance and expand upon this research. An initial course of action would involve conducting a more comprehensive analysis of the suboptimal performance exhibited by the LSTM model to gain a more profound understanding of the underlying factors that contribute to this outcome. Refining the architectural design and optimizing the training procedure may potentially enhance the model's capacity to effectively process textual data based on sequential patterns. Moreover, it is worth considering the expansion of the study to incorporate additional sophisticated machine learning models and techniques, such as Transformer models or ensemble methods. These alternatives may provide distinct viewpoints and potentially yield superior performance outcomes. An additional area for potential future research involves the incorporation of feature importance or interpretability metrics into the models, particularly in the case of neural networks. This would enable a more comprehensive understanding of the underlying learning processes and provide valuable insights.

Ultimately, the application of these models to diverse review types or alternative forms of textual data has the potential to yield more comprehensive insights regarding the extent to which these algorithms can be generalized. The objective would encompass not only attaining a high level of accuracy, but also constructing models that provide valuable insights into the fundamental patterns and structures within the data. This would consequently contribute to the advancement of comprehension regarding customer sentiment in online reviews. Hence, the ongoing trajectory initiated by this study remains unfinished, and the discoveries presented herein establish a basis and catalyst for forthcoming scholarly investigations.

References

[1] Das, B., & Chakraborty, S. An Improved Text Sentiment Classification Model Using TF-IDF and Next Word Negation. arXiv preprint arXiv:1806.06407, cs.CL. 2018.

[2] Li, X., Sun, X., Xu, Z., & Zhou, Y. Explainable Sentence-Level Sentiment Analysis for Amazon Product Reviews. arXiv preprint arXiv:2111.06070, cs.CL. 2021.

[3] Das, M., Selvakumar, K., & Alphonse, P. J. A. A Comparative Study on TF-IDF feature Weighting Method and its Analysis using Unstructured Dataset. arXiv preprint arXiv:2308.04037, cs.CL.2023.

[4] Guda, B. P. R., Srivastava, M., & Karkhanis, D. Sentiment Analysis: Predicting Yelp Scores. arXiv preprint arXiv:2201.07999, cs.LG. 2020.

[5] Khan, M., & Malik, K. Sentiment Classification of Customer's Reviews About Automobiles in Roman Urdu. In Advances in Intelligent Systems and Computing,2018, 630-640.

[6] Kazhuparambil, S., & Kaushik, A. Cooking Is All About People: Comment Classification On Cookery Channels Using BERT and Classification Models (Malayalam-English Mix-Code). arXiv preprint arXiv:2007.04249, cs.CL.,2020.

[7] Krishnan, A. B. H. Unmasking Falsehoods in Reviews: An Exploration of NLP Techniques". arXiv preprint arXiv:2307.10617, cs.IR. 2023.

[8] Radford, A., Jozefowicz, R., & Sutskever, I. Learning to Generate Reviews and Discovering Sentiment. arXiv preprint arXiv:1704.01444, cs.LG.2017.

[9] Mir, A. Q., Khan, F. Y., & Chishti, M. A. Online Fake Review Detection Using Supervised Machine Learning And BERT Model. arXiv preprint arXiv:2301.03225, cs.CL.2023.

[10] Shrestha, N., & Nasoz, F. Deep Learning Sentiment Analysis of Amazon.Com Reviews and Ratings". International Journal on Soft Computing, Artificial Intelligence and Applications, 2019, 8(1), 01-15.

[11] Minaee, S., Azimi, E., & Abdolrashidi, A. A. Deep-Sentiment: Sentiment Analysis Using Ensemble of CNN and Bi-LSTM Models. arXiv preprint arXiv:1904.04206, cs.CL. 2019.

[12] Krishnan, J., Purohit, H., & Rangwala, H. Diversity-Based Generalization for Unsupervised Text Classification under Domain Shift". arXiv preprint arXiv:2002.10937, cs.LG. 2020.

[13] Saifullah, S., Fauziyah, Y., & Aribowo, A. S. Comparison of machine learning for sentiment analysis in detecting anxiety based on social media data. Jurnal Informatika, 2021, 15(1), 45.

[14] Feng, H., & Lin, R. Sentiment Classification of Food Reviews. arXiv preprint arXiv:1609.01933, cs.CL.2016.

[15] Dasgupta, S., & Sen, J. A Framework of Customer Review Analysis Using the Aspect-Based Opinion Mining Approach. arXiv preprint arXiv:2212.10051, cs.CL.2022.

[16] So, C. What Emotions Make One or Five Stars? Understanding Ratings of Online Product Reviews by Sentiment Analysis and XAI. arXiv preprint arXiv:2003.00201, cs.AI. 2020.