

The development of Boeing aircraft wing design to reduce aircraft energy consumption

Xi Lin*

Guangdong Experimental High School, Guangzhou, China

* Corresponding Author Email: liusitong@ldy.edu.rs

Abstract. This paper comprehensively and deeply studies Boeing's innovative measures in the field of wing design, improving flight efficiency and reducing energy consumption by optimizing wing structures. The article outlines the key role of wing design in aircraft performance and points out that optimizing wing design is of great significance for improving fuel efficiency and reducing carbon emissions. Subsequently, the article analysed in detail the latest developments in the wing design of Boeing aircraft, including the use of advanced technologies such as angled winglets, bipinnate winglets, and shark fin winglets. These designs effectively reduce flight drag and improve lift efficiency by improving the aerodynamic performance of the wings, thereby achieving significant energy savings. In addition, the article also explores the impact of these improvements on airline operating costs, market competitiveness, and positive effects on environmental protection. Finally, the article looks forward to the future development trend of Boeing aircraft in the field of wing design.

Keywords: lift coefficient, drag coefficient, flow separation.

1. Introduction

Boeing has a long history and profound technical accumulation in aerofoil design. Since the early days of aircraft, Boeing has been committed to the research and development of aerofoils, constantly exploring new ways to improve aircraft aerodynamic efficiency and reduce drag. With the advancement of science and technology, Boeing has gradually launched a series of advanced aerofoils such as Clark-Y aerofoils, laminar aerofoils, supercritical aerofoils and adaptive aerofoils. These aerofoil designs not only improve the performance of aircraft but also promote the development of the entire aviation industry. Boeing has always maintained continuous innovation in aerofoil design technology. In modern aircraft design, Boeing makes full use of advanced technologies such as computer fluid dynamics (CFD) to fine-tune and optimize aerofoils. For example, in the design of the Boeing 787 "Dream" aircraft, Boeing uses advanced composite materials and automatic variable camber aerofoil technology to enable the aircraft to maintain optimal aerodynamic performance in different flight stages. In addition, Boeing has also made a lot of innovations in auxiliary aerofoil designs such as winglets, further improving the fuel economy and environmental performance of aircraft. Boeing's aerofoil design technology has been widely used in its various aircraft products and has achieved remarkable market results. From narrow-body aircraft such as the Boeing 737 series to wide-body aircraft such as the Boeing 777 and Boeing 787 series, Boeing's wing design has played an important role [1]. These wing designs not only improve the aerodynamic efficiency of the aircraft but also reduce operating costs, bringing better economic benefits to customers. At the same time, Boeing's wing design technology has also been widely recognized and praised by airlines and aviation manufacturers around the world.

2. Basic aerodynamic principles of wing design

2.1. Lift coefficient

The lift coefficient is a dimensionless quantity defined as the ratio of the lift experienced by an object (such as a wing) to the product of the aerodynamic pressure and the reference areas. The lift coefficient of a wing is influenced by various factors, including wing shape and area, flight angle of attack, airspeed, and air density. The lift coefficient is one of the important indicators for evaluating

wing performance. In aircraft design, it is necessary to select appropriate aerofoils and angle of attack ranges based on the requirements of the flight mission to ensure that the aircraft can obtain sufficient lift in different flight states. Meanwhile, the lift coefficient is closely related to the drag coefficient of the aircraft. An excessively high lift coefficient may lead to increased drag, increased fuel consumption, and decreased flight performance [2].

Lift is a key factor in making an aircraft fly, and the core of aerofoil design is to create different pressure distributions on the upper and lower wing surfaces. When air flows through the wing, the upper surface airflow velocity is faster, and according to Bernoulli's principle, the upper surface air pressure is lower; The airflow velocity on the lower surface is relatively slow and the air pressure is high. This pressure difference creates lift. Different wing profiles such as straight wing, elliptical wing, rectangular wing, flutter wing, etc. can lead to different flow states of the airflow, thereby affecting the generation of lift. For example, elliptical wings have a high lift-to-drag ratio, but are difficult to manufacture; Although the lift distribution of straight wings is uniform, the lift efficiency is not high and the drag is relatively large; Fluttering wings can reduce lift loss by changing the shape of the wing surface, but they are complex to manufacture and require high structural strength. Leading edge slats and flaps are commonly used on aeroplanes to increase lift, which can further enhance the lift during low-speed flight. Leading edge slats can increase the curvature of the aerofoil and increase the lift coefficient; Flaps increase lift by increasing wing area and changing wing profile shape.

2.2. Drag coefficient

The drag coefficient of a wing is an important parameter that describes the magnitude and nature of the drag experienced by the wing during flight. It is a dimensionless quantity typically defined as the ratio of the drag experienced by the wing to the product of the aerodynamic pressure and the reference area, where the aerodynamic pressure is half the product of the air density and the square of the flight speed V . The drag coefficient of a wing is influenced by various factors such as wing shape, flight angle of attack, airspeed, surface roughness, air density and temperature, and the flight attitude and speed of the aircraft during flight. During flight, pilots usually adjust the aircraft's attitude and speed based on actual flight conditions to control the drag coefficient [3]. By reducing the angle of attack, lowering airspeed, or adopting other flight strategies, the drag coefficient can be lowered to reduce fuel consumption and extend endurance.

Resistance hinders the forward movement of an aircraft, and reducing resistance is crucial for improving flight efficiency. The drag coefficient of a wing is a complex parameter that is influenced by multiple factors. In the aircraft design and operation phase, it is necessary to fully consider these factors and take corresponding measures to optimize drag performance to improve flight efficiency and safety. For example, advanced computer simulation software can be used in the aircraft design phase to predict and optimize drag coefficients.

The pressure distribution on the wing refers to the magnitude and direction of the pressure exerted on various points on the surface of the wing. These pressures are mainly determined by the velocity changes generated when air flows through the wing, following the Bernoulli principle, where the pressure is lower in areas with higher flow velocity and higher in areas with lower flow velocity. Common wing pressure distribution: pressure difference between upper and lower surfaces, stagnation point, and minimum pressure point (stagnation point: located near the leading edge of the wing, is the point with the highest positive pressure, where the airflow velocity is zero. The minimum pressure point is the point with the highest negative pressure on the upper surface of the wing)

2.3. Flow separation

The flow separation of a wing refers to the phenomenon where, due to various factors such as wing shape, angle of attack, and velocity, the airflow no longer flows along the wing surface at certain locations (such as the trailing edge or upper surface of the wing), but instead forms vortices or separation zones, resulting in changes in the pressure distribution on the wing surface. The main

causes of wing flow separation are as follows: wing shape, angle of attack, velocity, and atmospheric conditions.

2.4. Stability

The stability of aircraft flight is a very important factor, and wing design has many impacts on aircraft stability, such as torsional stiffness and disturbance propagation. Generally, wings with higher torsional stiffness can better resist external disturbances and maintain aircraft stability. Wing design also affects the propagation speed of disturbances on the wing. Reasonable wing design can slow down the propagation speed of disturbances on the wing, thereby reducing the impact of disturbances on aircraft stability.

2.5. Stalling

The phenomenon of aircraft stalling is something that most people do not want to see, as it can lead to serious consequences. Stall refers to the phenomenon where the wings of an aircraft are unable to maintain sufficient lift to support its weight during a certain flight state, resulting in the aircraft descending. Under stall conditions, aerodynamic instability can affect the flight characteristics of an aircraft. Wing design directly affects the stall characteristics of the wing. The stall performance of different aerofoils may be significantly different at the same angle of attack. The factors that affect the stall characteristics of an aircraft in aerofoil design generally include leading-edge radius and thickness (the leading-edge radius and thickness of an aerofoil can affect the stall characteristics of the aircraft. An aerofoil with a larger leading-edge radius is less likely to stall because the airflow is more likely to remain attached at the leading edge.), and the ratio of wing tip chord length to wing root chord length (a wing with a larger tip to root ratio may enter a spiral state more suddenly and easily during stall).

3. The Historical Evolution of Boeing Wing Design and the influence of wing design on flight performance and energy consumption

3.1. Boeing 707

The Boeing 707 is Boeing's first successful jet airliner, featuring an aerofoil design that enhances the lift, effectively reducing take-off and landing speeds, and improving manoeuvrability and safety. During take-off and landing, greater lift helps reduce the required runway length and improve operational flexibility. The wing design of the Boeing 707 helps to reduce air resistance during flight, which is one of the key factors in improving fuel efficiency. Lower drag means that the aircraft consumes less thrust during flight, thereby reducing fuel consumption. The Boeing 707 can maintain a high lift-to-drag ratio during cruising, which means generating sufficient lift while minimizing the generation of drag. This design helps the aircraft maintain high fuel efficiency during long-term cruising.

3.2. Boeing 747

The Boeing 747 has many upgrades, and the wing design of the Boeing 747 also considers the need for noise control. The wing design of the Boeing 747 has been calculated and optimized to improve lift and stability. Its supercritical wing design not only helps provide sufficient lift during take-off and landing but also enables the aircraft to maintain a stable flight attitude during cruising. This design reduces the induced drag of the wings and improves the overall aerodynamic efficiency of the aircraft [4]. The Boeing 747 has effectively reduced noise during take-off, landing, and cruising by adopting a tapered winglet and a redesigned flap system. The wing design of the Boeing 747 also considers the requirements of load and balance, optimizing load and balance. Through reasonable wing layout and structural design, the aircraft can maintain stable flight performance under different load conditions, thereby ensuring the reliability and safety of the range.

3.3. Boeing 787

The Boeing 787 is Boeing's latest aircraft model. The wing design of the Boeing 787 helps reduce air resistance during flight. By optimizing the wing structure and adopting advanced technologies such as laminar flow nacelle technology, the Boeing 787 can maintain a low drag coefficient during cruising, thereby reducing fuel consumption. This design enables the Boeing 787 to save a significant amount of fuel and reduce operating costs during long-distance flights. In addition to its wing design, the Boeing 787 also utilizes lightweight composite materials and advanced engine technology, which further enhance the aircraft's fuel economy through its comprehensive application [5]. Compared with the old model aircraft, the fuel efficiency of the Boeing 787 has increased by about 20%, thanks to its comprehensive optimized design.

4. Challenges and Future Trends

4.1. Improving aerodynamic performance

Boeing needs to design more efficient aerofoils to maintain excellent lift-to-drag ratio and transonic performance over a wider range of flight speeds. This requires the aerofoil to automatically adjust its shape or characteristics at different flight stages to adapt to various aerodynamic conditions. For example, the design of transonic truss-supported wings is an example aimed at improving aerodynamic efficiency and fuel economy [6].

4.2. Materials Science

With the widespread application of composite materials in the aerospace industry, Boeing needs to address the manufacturing and application challenges of composite materials in wing design. Although composite materials have the advantages of being lightweight and high strength, their manufacturing process is complex, the cost is high, and the process requirements are extremely high. Boeing needs to continuously develop new composite materials and their manufacturing processes to reduce production costs and improve production efficiency.

4.3. Manufacturing process

Boeing needs to optimize the manufacturing process of aerofoils to ensure accuracy and reliability during the manufacturing process. This includes improving mould design, optimizing processing parameters, and enhancing automation levels. At the same time, Boeing also needs to pay attention to quality control and inspection techniques during the manufacturing process to ensure that the manufacturing quality of the aerofoil meets the design requirements.

As future aircraft develop towards higher speeds, longer ranges, lower noise, and lower emissions, Boeing needs to constantly adjust and optimize its wing design. For example, for hypersonic aircraft, their wing design needs to adapt to extreme aerodynamic conditions and high-heat environments; For green aircraft, their wing design needs to consider environmental requirements such as reducing noise and emissions. Boeing needs to closely monitor the development trends and technological requirements of future aircraft to adjust its wing design strategy promptly.

5. Summary

Improve aerodynamic performance (Improve the lift-to-drag ratio, Enhance transonic performance). Wing design directly affects the lift and drag characteristics of an aircraft. Through precise wing design, the lift-to-drag ratio of an aircraft can be significantly improved, which is the ratio of lift to drag, thereby reducing energy consumption during flight and improving fuel efficiency. For aircraft flying at supersonic speeds, wing design requires special consideration of the effects of supersonic shock waves. By adopting design methods such as supercritical aerofoils, the shock

resistance during supersonic flight can be reduced, and the supersonic performance of the aircraft can be improved.

Reduce the weight of the aircraft (Application of lightweight materials, Improve structure and layout). With the advancement of materials science, composite materials have been widely used in aircraft manufacturing. In wing design, by selecting composite materials reasonably, the weight of the wing can be significantly reduced while ensuring structural strength, thereby reducing the overall weight of the aircraft and improving flight efficiency. Wing design also involves optimizing the structural layout of the wing. Through reasonable layout design, the manufacturing and maintenance costs of the wing can be reduced, while improving the stiffness and stability of the wing.

Improve the safety of aircraft during flight (Enhance the stability of flight, Improve the manoeuvrability of aircraft). Wing design has a significant impact on the stability of aircraft. By optimizing the aerodynamic characteristics of the aerofoil, the longitudinal and lateral stability of the aircraft can be enhanced, improving flight safety. Wing design also involves the manoeuvrability of the aircraft. Through reasonable wing design, the control response characteristics of the aircraft can be improved, and the accuracy and flexibility of control can be enhanced, thereby reducing the difficulty and risk of pilot misoperation.

Reference

- [1] Olason, M. L., & Norton, D. A. Aerodynamic design philosophy of the Boeing 737. *Journal of Aircraft*, 1966, 3 (6), 524-528.
- [2] Kweon, J., & Choi, H. Sectional lift coefficient of a flap** wing in hovering motion. *Physics of Fluids*, 2010, 22 (7).
- [3] Sadraey, M., & Müller, D. Drag force and drag coefficient. M. Sadraey, *Aircraft Performance Analysis*. VDM Verlag Dr. Müller. 2009.
- [4] Abdel-Raheem, A. A. M., Hanna, P. A. S., & Abdel-Hameed, I. A. M. Aerodynamic Study of Boeing 747-400 Airfoil.
- [5] Abdulai, K., Bergquist, J., Julien, A., Hu, N., Yilmaz, S., & Yoon, B. S. Boeing 787-Challenges in Managing Innovation. 2011.
- [6] Lee, Y. G., Kim, C. W., & Shim, J. Y. Aerodynamic Analysis Of Various Winglets. *Aerospace Engineering and Technology*, 2008, 7 (1), 24-29.