

# Application of 3D Bioprinting Technology in Tissue Engineering

Yibing Yang \*

Hengshui Zhizhen Middle School, Hengshui, China

\* Corresponding Author Email: fenyia@ldy.edu.rs

**Abstract.** As an emerging method in tissue engineering, 3D bioprinting technology has shown great potential in addressing challenges faced by traditional medicine. This review discusses the basic principles of 3D bioprinting technology, the primary methods involved, and the characteristics of bio-inks, while exploring its applications in tissue engineering. The main printing techniques include inkjet bioprinting, micro-extrusion bioprinting, and laser-assisted bioprinting, each with its own specific advantages and application areas. As the core component of this technology, bio-ink types and properties significantly influence the printing outcomes. This paper focuses on the specific applications of 3D bioprinting in areas such as microtia treatment, thyroid reconstruction, and skin regeneration, which demonstrate the unique advantages of this technology in creating complex tissue structures and functional organs. Despite the promising outlook of 3D bioprinting, numerous challenges remain in translating laboratory research to clinical applications, such as improving the functionality and long-term viability of printed tissues and addressing immune rejection issues. In the future, advancements in this technology may focus on multi-material and multi-cell-type printing, optimization of bio-inks, and integration with other advanced technologies. Overall, 3D bioprinting technology is expected to bring revolutionary changes to tissue engineering and regenerative medicine, offering more personalized and effective treatment options for patients.

**Keywords:** 3D bioprinting, tissue engineering, bio-ink, regenerative medicine, soft tissue repair.

## 1. Introduction

Tissue engineering and regenerative medicine have long been areas of significant interest in the development of modern medicine. Traditional tissue repair techniques, particularly in addressing skin injuries, primarily rely on skin grafts. However, this approach presents numerous limitations and challenges. First, skin grafts must be sourced from donors, which means that available grafts are limited. Secondly, more severe skin injuries often require a complete skin structure, including the epidermis, dermis, and subcutaneous tissue, making it even more challenging to find suitable grafts. Furthermore, even when transplantation is successful, improper post-operative care can lead to pigmentation issues and scarring, affecting the patient's quality of life.

In response to these challenges, researchers have been seeking more advanced and effective methods for tissue repair. In recent years, with the rapid development of biomedical and life sciences, 3D bioprinting technology has matured and brought new hope to fields such as soft tissue repair and skin regeneration. 3D bioprinting technology, developed from traditional 3D printing, combines computer-aided 3D imaging and multi-layer continuous printing principles to precisely fabricate complex biological structures. These structures can be designed to mimic the shape, biological function, and specific microenvironment of cells.

This technology not only provides new tools for tissue engineering but also paves the way for personalized medicine. Through 3D bioprinting, researchers can create functional three-dimensional biological constructs and regenerative medicine models in vitro, which can be used not only in fundamental research but also directly in clinical treatments. From the treatment of microtia to thyroid reconstruction and the repair of large skin injuries, 3D bioprinting technology has shown great potential.

This review aims to provide a comprehensive overview of the applications of 3D bioprinting technology in tissue engineering, including its underlying principles, bio-ink selection and properties, and specific application cases in various fields. By reviewing and analyzing current research progress,

we hope to offer readers a clear panorama of 3D bioprinting's applications in tissue engineering and to explore its future development direction and potential clinical applications.

## **2. Overview of 3D Bioprinting Technology**

### **2.1. Characteristics of 3D Bioprinting Technology**

3D bioprinting technology is an innovative application that has developed from traditional 3D printing. Its uniqueness lies in the use of biological materials or cells as "printing ink," enabling the creation of complex biological structures with both functionality and three-dimensional form. This technology can be used to manufacture biomedical products such as in vitro three-dimensional biological constructs and regenerative medicine models. More importantly, 3D bioprinting technology allows printing based on requirements such as biomimetic morphology, biological functionality, and specific cellular microenvironments, providing a powerful tool for tissue engineering and regenerative medicine [1].

### **2.2. Main 3D Bioprinting Methods**

#### **2.2.1. Inkjet Bioprinting**

Inkjet bioprinting relies primarily on acoustic or thermal energy to form and deposit droplets of bio-materials. Acoustic inkjet printing uses acoustic radiation force and ultrasonic fields to eject droplets from the air-liquid interface. This method's advantage is its ability to avoid the effects of heat and pressure on biological materials, allowing precise control of droplet size and preventing nozzle clogging. However, this method poses some limitations on the viscosity of the printable materials, which can be challenging in certain applications.

In contrast, thermal inkjet printing generates pressure pulses through electrically heated printheads, causing droplets to be ejected from the nozzle. This method is characterized by its high printing speed, typically taking only about 20 microseconds. Although heat is applied, the brief heat transfer time ensures minimal impact on the cells, allowing cell viability to exceed 95%, making thermal inkjet printing a promising technique in 3D bioprinting.

#### **2.2.2. Micro-extrusion Bioprinting**

Micro-extrusion bioprinting is a technique that melts thermoplastic materials using a heater, then extrudes them through a micro-nozzle. In this process, the material is drawn into filament form, fed into a heated extrusion head, and melted before being extruded through the nozzle. This method is relatively simple, cost-effective, and easy to maintain and operate. Additionally, micro-extrusion bioprinting offers high flexibility, as different nozzles can be swapped to meet diverse printing needs, and it operates at a faster speed compared to other methods.

However, this technique faces certain challenges, such as lower cell viability, reduced printing resolution, and a higher risk of contamination. To overcome these limitations, researchers have developed shear-thinning hydrogels, which exhibit reduced viscosity with increased shear rate during printing, protecting cells from high shear stress. Examples of such bio-inks include gelatin and its derivatives, as well as decellularized extracellular matrix (dECM) hydrogels, which are widely used in 3D bioprinting for tissue engineering [2].

#### **2.2.3. Laser-Assisted Bioprinting**

Laser-assisted bioprinting is a technology that uses laser-induced polymerization or crosslinking of photosensitive materials to achieve high-precision three-dimensional positioning of cells and bio-materials. The greatest advantage of this method is its high precision, offering micron-level printing resolution to meet the demands of different cellular printing resolutions. Additionally, laser-assisted bioprinting features high cell viability, a wide range of compatible biomaterials, and a high degree of automation. These characteristics make laser-assisted bioprinting particularly suitable for tissue engineering applications that require high-precision positioning.

### 3. Bio-ink

#### 3.1. Definition and Types of Bio-ink

In 3D bioprinting technology, bio-ink is a core component. Bio-ink generally refers to a solution mixture, often in the form of hydrogels, containing one or more biological materials, which encapsulate different types of cells during the bioprinting process. This special "ink" provides a three-dimensional microenvironment that supports cell survival and function.

Based on their function and application, bio-inks can be categorized into several main types. The most fundamental is Matrix Bioink, which supports and protects cells in the form of a hydrogel, providing an environment conducive to cell survival and growth. This type of bio-ink forms the basic material for most bioprinting applications and is indispensable in tissue engineering.

Support Bioink primarily serves to maintain the structure and integrity of the printed constructs. It typically exhibits good mechanical properties, making it suitable for printing tissues such as muscles, bones, and cartilage, which require a certain level of rigidity and strength.

Another important type is Sacrificial Bioink. This bio-ink provides temporary support during the printing process but is removed afterward. Its main role is to ensure the stability of complex structures during printing and then be removed to form the desired final construct.

#### 3.2. Material Selection for Bio-ink

The selection of bio-ink materials is crucial for the success of 3D bioprinting. Currently, four major types of bio-ink materials are widely studied and applied.

Natural hydrogel bio-inks are made from natural biological materials, such as collagen and fibrin. These bio-inks have excellent biocompatibility and can effectively mimic the natural environment of cells, promoting cell growth and function. Additionally, natural hydrogel bio-inks tend to degrade quickly, facilitating tissue remodeling and regeneration. However, their mechanical properties are relatively weak, which may limit their application in scenarios that require higher strength.

Synthetic hydrogel bio-inks are chemically synthesized. Their greatest advantage lies in their superior mechanical properties and tunability. Researchers can control the physical and chemical properties of synthetic hydrogels by adjusting the synthesis process to meet the specific needs of different tissue types. However, synthetic hydrogels may be less biocompatible than natural hydrogels, which is an important factor to consider in their application.

To combine the advantages of both natural and synthetic hydrogels, researchers have developed composite hydrogel bio-inks. These bio-inks are made from a mixture of two or more hydrogels, offering improvements in both mechanical performance and biocompatibility. Composite hydrogel bio-inks provide researchers with greater flexibility, allowing material properties to be tailored to specific application needs.

Lastly, photosensitive bio-inks are an emerging type of bio-ink. These bio-inks contain photo initiators, which can be activated by light exposure to induce a transition from sol to gel state. The advantages of photosensitive bio-inks include their rapid crosslinking speed and high spatial resolution, making them particularly suitable for creating tissues with complex microstructures.

#### 3.3. Characteristics of an Ideal Bio-ink

When selecting or designing bio-inks, several key characteristics must be considered to ensure their effective application in 3D bioprinting. First, an ideal bio-ink should possess a robust tissue structure and a tunable mechanism to retain that structure. This means the bio-ink should maintain its shape during printing and provide adequate support afterward until the cells can produce their own extracellular matrix.

Second, the stabilization and gelation process of the bio-ink should be adjustable. This characteristic is crucial for maintaining shape during the printing process. A tunable gelation process allows researchers to modify the rheological properties of the bio-ink according to different printing needs.

Biocompatibility is another key characteristic. An ideal bio-ink should mimic the biological microenvironment, providing cells with a favorable environment for survival and function. Additionally, the bio-ink should have controllable biodegradability to coordinate with the tissue remodeling and regeneration process.

The possibility of chemical modification is also an important consideration. Chemically modifiable bio-inks can be enhanced by adding specific bioactive molecules, such as those that promote cell adhesion or stimulate cellular behaviors.

Finally, to enable large-scale production and application, an ideal bio-ink should have minimal batch-to-batch variation. This means the preparation process should be reproducible, consistently yielding materials with the same properties.

## **4. Applications of 3D Bioprinting in Tissue Engineering**

As an emerging method in tissue engineering, 3D bioprinting has demonstrated immense potential in various medical fields. This chapter delves into its specific applications in the treatment of microtia, thyroid reconstruction, and skin regeneration, showcasing the unique advantages of this technology in addressing complex medical challenges.

### **4.1. Treatment of Microtia**

Microtia is a congenital deformity characterized by underdeveloped or absent external ears. Traditional treatments primarily rely on autologous rib cartilage grafts or synthetic polymer materials for auricular reconstruction, but these methods often encounter issues such as limited donor tissue and significant surgical trauma. The advent of 3D bioprinting technology offers new possibilities for microtia treatment.

Kim et al. demonstrated the application of 3D printing in the treatment of microtia by combining 3D-printed implants with traditional surgical techniques [3]. Their approach followed Nagata's two-stage total ear reconstruction principle, with the 3D-printed implants replacing autologous tissue. In the first stage, a W-shaped incision was made to reposition the affected ear lobe and prepare a cavity for the implant. A 3D-printed implant was then inserted into the cavity. In the second stage (approximately three months later), another incision was made at the rear of the initial implant to place a second 3D-printed implant, which was used to elevate the reconstructed ear. Finally, a temporalis fascia was applied over the new implant, and a full-thickness skin graft was placed on the fascia.

This method offers several advantages, including the ability to customize the implant's shape and size precisely to match the patient's facial features, resulting in better aesthetic outcomes. Additionally, by avoiding the use of autologous rib cartilage, surgical trauma and the risk of complications are significantly reduced. However, long-term follow-up studies are still required to evaluate the long-term outcomes and safety of this technique.

### **4.2. 3D-Printed Thyroid**

The thyroid is the largest endocrine gland in the body and plays a vital role in regulating metabolism. Thyroid dysfunction can lead to severe health issues, and traditional treatments such as medication or surgery often fail to fully restore thyroid function. 3D bioprinting offers an innovative approach to thyroid function reconstruction.

Arguchinskaya et al. explored the possibility of 3D-printed thyroid tissue [4]. They constructed a thyroid cartilage model based on CT imaging data and used 3D printing technology to manufacture thyroid tissue (Fig. 1). This 3D-printed thyroid was successfully transplanted into experimental animals, resulting in a significant increase in thyroid hormone levels post-transplantation. More importantly, histological evaluation confirmed that the bioprinted thyroid matured successfully and integrated well with the host tissues.

The significance of this research lies in demonstrating the potential of 3D bioprinting to produce functional endocrine organs. This not only offers new therapeutic hope for patients with thyroid dysfunction but also paves the way for the regeneration and reconstruction of other endocrine organs. However, there are still many challenges to overcome before clinical application, such as ensuring that the printed thyroid can stably secrete hormones over the long term and avoiding immune rejection.




**Figure 1.** 3D printing of thyroid gland based on medical images [4].

#### 4.3. 3D-Printed Skin

The skin is the largest organ of the human body and is highly susceptible to injury. For severe skin damage, traditional treatments primarily rely on skin grafting, but this approach is often limited by the availability of donor tissue and the formation of scars. 3D bioprinting offers a novel solution for repairing large-scale skin injuries.

Weng et al. investigated the application of 3D bioprinting in skin tissue engineering [5]. They highlighted that 3D-printed skin consists of multiple layers, simulating the complex structure of natural skin, including the epidermis, dermis, and subcutaneous layers. The advantage of this method is its ability to precisely control the thickness and composition of each layer, better meeting the specific needs of different skin areas.

However, there are still some limitations to 3D-printed skin. One of the most notable challenges is that current technology cannot include structures such as sweat glands, hair follicles, and sebaceous glands in the printed skin. These structures are critical for the normal physiological functions of the skin. For example, sweat glands play an important role in thermoregulation and produce substances like urea, lactic acid, and creatine that inhibit bacterial growth on the skin surface. Thus, reconstructing these complex accessory structures in 3D-printed skin has become a key research direction.

## 5. Conclusion

As an innovative approach in the field of tissue engineering, 3D bioprinting demonstrates enormous potential. This paper has reviewed the fundamental principles, key methods, and characteristics of bioinks, as well as explored its applications in microtia treatment, thyroid reconstruction, and skin regeneration.

The core advantage of 3D bioprinting lies in its ability to precisely control the spatial distribution of cells and biomaterials to construct complex tissue structures. In microtia treatment, it allows for the creation of personalized auricular implants; in thyroid reconstruction, it shows potential in

fabricating functional endocrine organs; and in skin regeneration, it offers promising solutions for repairing large-scale injuries.

Bioink is a critical component of this technology. From natural to synthetic hydrogels, and from composite to light-sensitive bioinks, researchers have continuously explored new materials and formulations to balance biocompatibility, mechanical properties, and printability.

Despite its broad prospects, 3D bioprinting faces several challenges before transitioning from laboratory research to clinical application, such as improving the functionality and long-term viability of printed tissues, addressing immune rejection, and reconstructing vascular networks within the printed tissues.

In the future, the development of this technology may focus on multi-material and multi-cell type printing, bioink optimization, integration with other advanced technologies, improvements in printing equipment, and advancements toward standardization and scalable applications.

In summary, 3D bioprinting is reshaping the future of tissue engineering and regenerative medicine. As the related challenges are gradually overcome, this technology has the potential to provide more personalized, efficient, and safe treatment options, significantly improving human health. However, achieving this goal will require continued efforts and innovation from multidisciplinary researchers.

## References

- [1] Gungor-Ozkerim P S, Inci I, Zhang Y S, Khademhosseini A, Dokmeci M R. Bioinks for 3D bioprinting: an overview. *Biomater Sci*, 2018, 6 (5): 915 - 946.
- [2] Wang Z, Wang L, Li T, et al. 3D bioprinting in cardiac tissue engineering. *Theragnostic*, 2021, 11 (16): 7948 - 7969.
- [3] Kim M, Kim Y J, Kim Y S, et al. One-Year Results of Ear Reconstruction with 3D Printed Implants. *Yonsei Med J*, 2024, 65 (8): 456 - 462.
- [4] Arguchinskaya N V, Beketov E E, Kisel A A, et al. The Technique of Thyroid Cartilage Scaffold Support Formation for Extrusion-Based Bioprinting. *Int J Bioprint*, 2021, 7 (2): 348.
- [5] Weng T, Zhang W, Xia Y, et al. 3D bioprinting for skin tissue engineering: Status and perspectives. *J Tissue Eng*, 2021, 12: 20417314211028574.