Enhancing Solar Cell Efficiency through Quantum Dots and Emerging Photovoltaic Technologies

Haitong Wang, Qiyu Su, and Tianyu Weng *

Chongqing Depu Foreign Language School, Chongqing, China

* Corresponding Author Email: wty1901305522@gmail.com

Abstract. As the world strives for carbon neutrality, solar energy has become a central focus for reducing emissions. However, the efficiency of solar cells is constrained by the Shockley-Queisser limit, limiting their broader adoption. Quantum dots (QDs), nanoscale semiconductor particles with unique size-dependent properties, offer a promising solution to enhance solar cell performance by improving light absorption and enabling multiple exciton generation. This paper explores the application of QDs in improving solar cell efficiency, focusing on their ability to broaden the absorption spectrum and generate multiple electron-hole pairs per photon. Various synthesis methods—such as colloidal synthesis, epitaxial growth, and chemical vapor deposition (CVD)—are discussed, highlighting how each impacts the size, shape, and properties of QDs. The paper reviews key types of QD-based solar cells, including QD-sensitized, thin-film, and perovskite-enhanced cells, which have demonstrated significant improvements in power conversion efficiency. Additionally, challenges such as high production costs, stability issues, and the toxicity of lead-based QDs are addressed, along with emerging trends in non-toxic alternatives and potential commercialization in areas like building-integrated photovoltaics (BIPV) and wearable electronics.

Keywords: Quantum Dots, solar cell, photovoltaics.

1. Introduction

Today, where environmental consciousness is steadily increasing, over 110 countries have committed to achieving carbon neutrality by 2050. In the quest to reduce emissions, renewable energy sources like solar power have garnered significant attention from politicians and scientists worldwide, with solar cells, or photovoltaics (often referred to as solar panels), emerging as a leading solution. Despite their potential, however, solar cells face several challenges that hinder their widespread adoption compared to other energy-generation technologies, such as nuclear power or hydroelectric dams. A major limitation is that solar cells are dependent on daylight, and the intensity of sunlight as well as its duration varies significantly by geographical location.

The most critical challenge, however, lies in the intrinsic limitation of their photoelectric conversion efficiency, which is constrained by the renowned Shockley-Queisser limit. This theoretical limit, first proposed in 1961, asserts that the maximum conversion efficiency for an ideal solar cell is 33.7%. Despite more than half a century of technological advancements and experimental efforts, surpassing this efficiency threshold remains an elusive goal in commercial solar cell technologies. Quantum dots (QDs), a new class of semiconductors, are nanoscale particles typically ranging in size from 1 to 10 nanometers. Due to their size-dependent optical and electronic properties, quantum dots have emerged as a promising material for enhancing solar cell performance, with the potential to overcome the Shockley-Queisser limit. Their unique features, such as tunable bandgaps that vary with size, make them ideal candidates for boosting the efficiency of photovoltaic devices.

Research on quantum dot-based solar cells is extensive and diverse. While some studies focus on the synthesis and characterization of quantum dots, others explore various materials and approaches to harness their potential in photovoltaics. Notably, perovskite quantum dots have shown substantial progress in laboratory settings, though much work remains to fully unlock their potential for practical applications. In addition to their application in solar cells, quantum dots have shown promise in a wide range of fields, including medical diagnostics and quantum dot light-emitting diode (QLED)

displays. This article will specifically focus on the role of quantum dots in enhancing solar cell technology, discussing their basic principles, synthesis methods, key challenges, and future potential.

2. Understanding Quantum Dots

2.1. Structure and Properties of Quantum Dots

QDs are semiconductor particles in the nanoscale range, typically with diameters between 2 and 10 nanometers. Their unique electronic and optical properties arise from a phenomenon known as quantum confinement, where the movement of electrons and holes is restricted within a confined space. This confinement leads to the formation of discrete energy levels, unlike in bulk materials where energy levels are continuous. As the size of the quantum dots decreases, the energy gap between the valence and conduction bands widens, resulting in a blueshift in their absorption and emission spectra. In other words, smaller quantum dots absorb and emit light at shorter wavelengths.

These tunable properties make quantum dots particularly valuable in solar cell applications, as their absorption spectrum can be precisely adjusted by controlling the particle size. This ability to manipulate the absorption spectrum enables quantum dots to capture light across a wide range of wavelengths, thereby increasing the efficiency of solar energy conversion. Additionally, the high surface-to-volume ratio of quantum dots enhances charge separation and transport, further improving the overall efficiency of solar cells.

Several types of quantum dots are commonly used in solar cell technologies. Cadmium-based quantum dots, such as cadmium selenide (CdSe) and cadmium telluride (CdTe), are well-known for their high quantum yields and flexible absorption properties. However, the toxicity of cadmium presents significant environmental and safety concerns, limiting the broader use of these materials. Lead sulfide (PbS) quantum dots offer similar optical properties but also face restrictions due to their toxicity. In response to these challenges, researchers have developed non-toxic alternatives, such as indium phosphide (InP) and copper indium sulfide (CIS), which are continuously being enhanced to offer safer and more sustainable solutions for solar cell applications.

2.2. Synthesis Methods

Quantum dots (QDs) can be synthesized using a variety of methods, with the most commonly used techniques being colloidal synthesis, epitaxial growth, and chemical vapor deposition (CVD). Each method has distinct advantages and impacts the size, shape, and properties of the resulting quantum dots, making the choice of synthesis technique critical for tailoring QDs to specific applications.

Colloidal synthesis is the most widely used method for producing quantum dots due to its simplicity and scalability. This method involves the nucleation and growth of nanoparticles in a liquid medium, where a precursor solution is rapidly injected into a hot solvent. For example, the process of synthesizing cadmium selenide (CdSe) is depicted in Figure 1 [1]. In this method, a cadmium compound is heated to 320 °C and dissolved in an organic solvent. Simultaneously, another organic solvent containing a selenium compound is prepared at room temperature. The combination of these solutions results in supersaturation. As the temperature decreases, existing crystals begin to grow, while no further nucleation occurs. When the temperature drops to approximately 220 °C, crystal growth halts. To enhance stability, a small amount of zinc sulfide can be injected into the reaction vessel, coating and insulating the quantum dots from the environment. The size of the resulting quantum dots is influenced by several factors, including pH, temperature, and reaction duration.




Figure 1. Colloidal synthesis of CdSe (where trioctylphosphine (TOP), trioctylphosphine oxide (TOPO)) [1]

Epitaxial growth is another technique used to produce high-quality quantum dots with controlled shapes and sizes on a substrate. In this process, a thin film of material is deposited onto a crystalline substrate under a vacuum environment. Advances in techniques like in-situ hybrid molecular beam epitaxy have improved the performance of epitaxial growth by addressing issues such as lattice and thermal mismatches. For example, five-layer GaAs quantum dots produced using this method have demonstrated excellent performance [2]. The properties of quantum dots synthesized via epitaxial growth are influenced by several factors, including the growth conditions (temperature and pressure), precursor concentration, and the thickness of the epitaxial layers.

Chemical vapor deposition (CVD) is a process that involves the decomposition of gaseous precursors on a heated substrate to form a solid material. This method is notable for its ability to produce uniform, high-quality thin films, making it ideal for synthesizing quantum dots directly on a substrate. The gas-phase nature of the reaction allows for precise control over the composition and morphology of the quantum dots by adjusting the precursor gases and reaction conditions. CVD is especially attractive for large-scale quantum dot production, making it a viable option for commercial applications due to its scalability.

Each of these synthesis methods significantly influences the size, shape, and properties of the resulting quantum dots, making the choice of method crucial in optimizing their performance for various applications, particularly in fields such as solar energy, optoelectronics, and bioimaging.

3. Quantum Dots in Photovoltaics

3.1. Mechanism of Quantum Dots Improve Solar Cell Efficiency

CVD is a process that involves the decomposition of gaseous precursors on a heated substrate to form a solid material. It is particularly valued for its ability to produce uniform, high-quality thin films, which can be used to synthesize quantum dots directly on a substrate. The gas-phase nature of the CVD reaction allows for precise control over the composition and morphology of the quantum dots by adjusting the precursor gases and reaction conditions. This method is highly attractive for large-scale quantum dot production for commercial applications due to its scalability.

QDs contribute significantly to improving solar cell efficiency through the quantum confinement effect, which enables them to generate more than one electron-hole pair per absorbed photon. This phenomenon, known as multiple exciton generation (MEG), allows a single high-energy photon to split into two or more photons of lower energy, each capable of generating an electron-hole pair. MEG improves the energy utilization per photon, potentially leading to a marked increase in the overall efficiency of solar cells.

Additionally, quantum dots can broaden the absorption spectrum of solar cells. By adjusting the size of the quantum dots, it is possible to design QDs with different absorption wavelengths,

extending the absorption spectrum range of the entire solar cell. This enables the solar cell to capture a wider range of the solar spectrum, from ultraviolet to visible light, and into the near-infrared region. As a result, the opportunities for photon absorption are enhanced, along with overall energy conversion efficiency. Theoretical studies suggest that perovskite quantum dot-based solar cells could potentially exceed the Shockley-Queisser efficiency limit of 33.7% for single-junction cells [3], especially with reduced thickness [4].

In solar cell applications, quantum dots can be integrated in two primary ways: as sensitizers in quantum dot-sensitized solar cells (QDSSCs) or as absorbers in heterojunctions. In QDSSCs, quantum dots absorb light and inject electrons into a wide-bandgap semiconductor, thereby improving light absorption. In heterojunction solar cells, the high surface area and exceptional optical properties of quantum dots are leveraged to maximize light harvesting and enhance charge separation, thus improving the efficiency of solar energy conversion (Figure 2).




Figure 2. Schematic of perovskite quantum dot solar cells [4]

3.2. Types of Quantum Dots Solar Cells

QD solar cells leverage the unique properties of quantum dots to enhance solar energy conversion efficiency. There are three primary types of QD-based solar cell architectures: QDSSCs, quantum dot thin-film solar cells, and QD-enhanced perovskite solar cells. Each type employs quantum dots in distinct ways to improve performance in light absorption, charge separation, and overall efficiency.

In QDSSCs, quantum dots act as sensitizers, attached to a mesoporous semiconductor film, typically titanium dioxide (TiO_2). When light strikes the quantum dots, they absorb the photons and inject electrons into the semiconductor film, generating an electric current. The mesoporous structure of TiO_2 enhances the surface area for electron injection, facilitating efficient charge separation and transport, which ultimately improves the cell's performance.

In quantum dot thin-film solar cells, quantum dots serve as the primary light absorbers and charge carriers. The quantum dots are embedded in a thin film deposited directly onto a substrate. This architecture allows for a high surface area, which enhances charge separation and minimizes recombination losses. As a result, quantum dot thin-film solar cells offer improved performance by ensuring more efficient photon absorption and electron transport.

In QD-enhanced perovskite solar cells, quantum dots are integrated into perovskite layers to boost light absorption and charge separation. This hybrid approach combines the advantages of both quantum dots and perovskite materials. Over the past decade, advancements in this technology have significantly improved power conversion efficiency, increasing it from 3.8% in 2009 to an impressive 25.5% in recent years [5]. The enhanced light-harvesting capabilities and better charge dynamics offered by the quantum dots contribute to this dramatic improvement in efficiency.

Each of these QD solar cell architectures utilizes quantum dots in different ways to maximize light absorption, improve charge separation, and enhance overall energy conversion efficiency, making them a promising avenue for advancing solar energy technologies.

4. Challenges and Limitations

Although quantum dots offer promising potential for enhancing the efficiency of solar cells, several challenges still hinder their commercialization.

4.1. Preparation Methods

There are various methods for synthesizing quantum dots, with hot injections being the most commonly used. This method allows for precise control over the quantum dot structure by adjusting the temperature. However, hot injections require high temperatures and an inert atmosphere, which makes the process relatively demanding and drives up the cost of quantum dot synthesis. Other methods, such as microwave and ultrasonic synthesis, are simpler and require less time, but the quantum dots produced by these methods often exhibit significant surface defects. These defects can trap charge carriers, leading to a reduction in open-circuit voltage and making the quantum dots unstable when exposed to air and oxygen. To mitigate this, additional stabilizers, such as ligands or ionic compounds, are often required, which complicates the industrialization process [6].

4.2. Stability Issues

Due to their nanoscale size, quantum dots have a high proportion of atoms on their surface, leading to an increase in surface defects. These defects can trap excited electrons, which lowers the power conversion efficiency (PCE) of solar cells. Additionally, the large surface area-to-volume ratio of quantum dots results in a significant number of dangling bonds, making them highly reactive to water and oxygen. This reactivity can cause the quantum dots to decompose or undergo phase changes [6]. As a result, surface passivation becomes essential for stabilizing quantum dots and maintaining their performance.

4.3. Film-Making Processes

There are two main types of film-making processes for quantum dot solar cells: drop casting and spraying. In the drop casting method, quantum dot solution is deposited directly onto a substrate and allowed to evaporate, forming a quantum dot film. This method offers 100% material utilization and a simple process, but due to uneven evaporation rates and inconsistent film thickness, it is only suitable for small-area films. The spraying method, on the other hand, is faster and more manageable, making it ideal for producing large-area films. However, the technology for spray-heads is not yet fully developed, and the contact between the surface and film is often weak, leading to lower PCE. A newer technique, known as scraping, shows promise. In this method, quantum dot inks are applied to a substrate using a blade, resulting in a more stable film. The ink solvent helps to prevent the formation of defects, making scraping a highly anticipated technique for large-scale production [6].

4.4. Toxicity of Lead

Many of the most efficient quantum dots used in solar cells are lead-based due to their excellent performance and high multiple exciton generation (MEG) yield. Despite these advantages, the toxicity of lead cannot be overlooked. Lead exposure poses serious health risks, including damage to the nervous and immune systems, through inhalation or skin contact with lead particles. Additionally, lead contamination in soil can cause further harm to animals and water systems. To address this, researchers are investigating alternatives to lead-based quantum dots, such as replacing Pb^{2+} with Sn^{2+} or Ge^{2+}, which belong to the same group. However, these alternatives are prone to oxidation, and their PCE drops to around 16%. The presence of lead in quantum dots, particularly in perovskite quantum dot solar cells, is a significant obstacle to large-scale use, as the lead content exceeds the European Union's Restriction of Hazardous Substances (RoHS) limits [7].

5. Future Prospects and Developments

5.1. Emerging Trends in Quantum Dots Research

Since the concept of QDs was first proposed, their development has been continuously evolving. Today, numerous applications of quantum dots are emerging across various fields, demonstrating the impact of this advancement. In life sciences, luminescent materials and devices composed of semiconductor quantum structures have become prevalent. The size of these quantum dots is comparable to that of the dye molecules traditionally used, making them highly valuable in biomedical research.

A notable development is the discovery of CQDs in 2004, which belong to the family of carbon nanomaterials [8]. CQDs offer several key advantages, including affordability, high water solubility, and strong resistance to photobleaching. Remarkably, CQDs possess the ability to act as up conversion nanoparticles, absorbing photons with lower energy. This makes CQDs highly suitable for applications in energy storage systems, biological imaging, and beyond.

As global demand for energy storage continues to intensify, the development of renewable energy technologies cannot be overlooked. Among the emerging technologies are quantum dot-sensitized solar cells (QDSSCs) [9], which are regarded as a promising next-generation solution in photovoltaics. QDSSCs exhibit optoelectronic properties ideal for photovoltaic applications. Their flexible size and composition allow them to effectively match a wider solar spectrum, making them a suitable material for light absorption. Currently, QDSSCs have achieved power conversion efficiencies of up to 12%, which is still lower than that of traditional solid-state single-junction solar cells. However, advancements in other technologies, such as perovskite solar cells, are showing even greater potential for higher conversion efficiencies.

5.2. Potential for Commercialization

Quantum dots offer immense potential for commercialization across a wide range of applications, with BIPV being a standout example. Thanks to the flexibility and transparency of quantum dot solar cells, they can be seamlessly integrated into BIPV systems. These systems allow for the integration of solar cells into building surfaces, windows, and roofs, effectively transforming them into electricity-generating structures. This reduces the need for separate solar panel installations and enhances the aesthetic appeal of buildings. By carefully managing the coverage area, BIPV systems can also help minimize costs [10].

In addition to architectural applications, quantum dot solar cells have potential in wearable electronic devices. Their lightweight and flexible properties make them ideal for use in devices such as health monitors and other electronics that require continuous power. Quantum dot solar cells can provide a convenient, self-sustaining power source for these devices, contributing to the advancement of wearable technologies.

6. Conclusion

QDs represent a breakthrough technology with the potential to revolutionize the field of photovoltaics, offering solutions to the limitations of traditional solar cells, particularly in terms of efficiency. By leveraging the quantum confinement effect, QDs have the ability to broaden the absorption spectrum and generate multiple excitons from a single photon, paving the way for solar cells that could potentially exceed the Shockley-Queisser limit. Their tunable optical and electronic properties, along with various synthesis methods such as colloidal synthesis, epitaxial growth, and CVD, allow for precise control over size, shape, and functionality, making them highly versatile for different applications.

However, despite these advantages, several challenges hinder the commercialization of QD-based solar cells. The high cost of quantum dot synthesis, stability issues related to surface defects, and the toxicity of lead-based QDs remain significant obstacles. Researchers are actively exploring

alternative materials and surface passivation techniques to overcome these hurdles and make QD solar cells more practical for widespread use. Furthermore, innovations in film-making processes and the development of non-toxic QD materials hold promise for the future.

As renewable energy continues to grow in importance, quantum dots present a viable solution not only for increasing the efficiency of solar cells but also for diverse applications such as building-integrated photovoltaics (BIPV) and wearable electronic devices. While further research is needed to address current challenges, the potential for quantum dots to significantly enhance solar energy technologies remains promising. With ongoing advancements, QDs could play a critical role in the global transition toward cleaner, more efficient energy systems.

Authors Contribution

All the authors contributed equally and their names were listed in alphabetical order.

References

[1] Mohamed W A A, Abd El-Gawad H, Mekkey S, et al. Quantum dots synthetization and future prospect applications. Nanotechnology Reviews, 2021, 10 (1): 1926 - 1940.

[2] Zhang J Y, Wei W Q, Wang J H, et al. Epitaxial growth of InAs/GaAs quantum dots on {113}-faceted Ge/Si (001) hollow substrate. Optical Materials Express, 2020, 10 (4): 1045 - 1052.

[3] Li T, Dagenais M. Modified Shockley-Queisser limit for quantum dot solar cell/2015 IEEE 42nd Photovoltaic Specialist Conference (PVSC). IEEE, 2015: 1 - 4.

[4] Khalid M, Mallick T K. Stability and performance enhancement of perovskite solar cells: a review. Energies, 2023, 16 (10): 4031.

[5] Liu L, Najar A, Wang K, et al. Perovskite quantum dots in solar cells. Advanced Science, 2022, 9 (7): 2104577.

[6] Chi W, Banerjee S K. Application of perovskite quantum dots as an absorber in perovskite solar cells. Angewandte Chemie International Edition, 2022, 61 (9): e202112412.

[7] Khan J, Ullah I, Yuan J. CsPbI 3 perovskite quantum dot solar cells: opportunities, progress and challenges. Materials Advances, 2022, 3 (4): 1931 - 1952.

[8] Aghamali A, Khosravi M, Hamishehkar H, et al. Synthesis and characterization of highly efficient photoluminescent sunlight driven photocatalyst of N-Carbon Quantum Dots. Journal of Luminescence, 2018, 201: 265 - 274.

[9] Sahu A, Garg A, Dixit A. A review on quantum dot sensitized solar cells: Past, present and future towards carrier multiplication with a possibility for higher efficiency. Solar Energy, 2020, 203: 210 - 239.

[10] Duan L, Hu L, Guan X, et al. Quantum dots for photovoltaics: a tale of two materials. Advanced Energy Materials, 2021, 11 (20): 2100354.